



EXPERIENCE EASY. NO SETUP.
NO ADJUSTMENTS. NO WASTE.

BRADYPRINTER i5300

Industrial
Label Printer


Set up, switch out and print faster than you ever imagined with the BradyPrinter i5300 Industrial Label Printer. It's intuitive, auto-calibrating and precise, printing barcodes and small fonts on labels as small as 5.08 mm. With a solid, metal frame construction, it can handle both high-volume and high-mix labelling applications: electronics and product ID, wire and panel ID, lab ID and safety and facility ID.

Get fast and efficient precision printing for high-mix/high-volume labelling. Printer features quick label set up and no-waste material changeovers.

- 300 dpi; prints small fonts with precision
- Requires no calibration and no heat and speed setting adjustments
- 20-second material changeovers, 5.08 mm – 101.6 mm label widths
- Pauses, resumes and stores print jobs on printer in an adjustable queue with overwrite protection
- 178 mm colour touchscreen and built-in auto cutter
- Solid construction with an all-metal frame
- Intuitive and easy to operate

Easy - inside and out.

When it comes to the BradyPrinter i5300 Industrial Label Printer, everything's easy. Taking just seconds to set up and load, it offers a faster, easier start-to-print process. That's because it's designed for efficiency - no setup, no adjustments and no waste. Zero. Enjoy time-saving features like a print queue and interrupt function. Plus, get precision printing on 75 material types and over 1300 parts, with custom parts available. All this so you can reach your high-mix, high-volume printing goals. Ready? We told you it was easy.



Specifications

Model name	BradyPrinter i5300 Industrial Label Printer	Volume guidelines*	5,000+ labels per day. 5 days per week			Media alignment	Centre justified
Printhead/printing characteristics							
Print resolution	300 dpi model 600 dpi model	Print method	Direct transfer, thermal transfer			Cutter type/auto cutter	Auto cutter built-in (all models)
Print colour capability	Colour printing capability/single colour	Print job interrupt options	Resume print job where pause or interruption occurs, or select specific label in job			Printhead replacement	Field replaceable (with same dpi only)
Maximum print width (cross-web)	101.98 mm					Print on demand	Yes
Maximum print label length (down-web)	1.524 m	Print roller replacement	Field replaceable (T10 wrench required)			Print pause	Yes
Print speed	up to 177.80 mm/sec - die cuts (300 dpi) up to 254.00 mm/sec - continuous (300 dpi) up to 76.20 mm/sec - die cuts (600 dpi) up to 127.00 mm/sec - continuous (600 dpi)	Stand-alone print job list on printer	Yes - BradyWorkstation print jobs can be saved to printer for later on-printer selection and placement into a Print Queue. This function also write-protects the print jobs from unwanted editing.				
Interface							
Display type and size	Colour LCD touchscreen	Display size (diagonal)	177.80 mm				
Display resolution (h x w)	600 x 1024 pixels	Display status bar	Installed ribbon and label part numbers, amount of supplies remaining, Wi-Fi connection, Bluetooth connection, receiving data icon, ready state/error state				
Display languages	Bahasa Indonesia, Bahasa Melayu, Bulgarian, Chinese (simplified), Chinese (traditional), Croatian, Czech, Danish, Dutch, Estonian, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Slovakian, Slovenian, Spanish, Swedish, Turkish, Thai, Vietnamese						
Interface and connectivity							
PC connection port	1 x USB 2.0 hi-speed device port	Serial port	No	Ethernet	1 x Ethernet 100 BASE-T	Bluetooth	(wireless printer model only) Internal Bluetooth module (future functionality)
USB host ports	3 x USB 2.0 type A host port (1 front, 2 back)	SD card slot	No	Wireless	(wireless printer model only) Factory installed Wi-Fi 802.11b/g/n		
Fonts, graphics and barcodes							
Character sets	ASCII character set	Font types (resident)	Arial, Courier New, MS Gothic, Malgun Gothic, MingLiU, SimSun, Tahoma, Times New Roman, Trebuchet MS, Verdana			Barcode symbologies - linear	Code 39, Code 93, Code 128 A, B, C, Codabar, EAN-8, EAN-13, JAN-8, JAN-13, HIBC, Interleaved 2 of 5, Interleaved 2 of 5 w check digit, MSI Plessey, UPC-A
Font types (storable to printer)	TrueType fonts storable to printer via jump drive	Graphic elements	Arrow, line, rectangle, square, circle, ellipse, diamond, not, star, triangle, seal, cross				
Font attributes	Bold, italic, underlined	Graphic formats	BMP, GIF, JPEG, PNG				
Barcode symbologies - 2D	Aztec, DataMatrix, QR Code, PDF-417	Barcode attributes	Sizing: variable in height and ratio Rotation: 0°, 90°, 180°, 270° human-readable and human-readable location density				
Media and ribbon characteristics							
PrintSmart technology	Yes - Reads datachip on supplies for no-waste printing, requires no calibration, has pre-optimized energy and speed settings and features auto label setup in Brady software	Media loading/handling	Labels: In cartridge, drops into place, 15-second changeover Ribbon: In cartridge, snaps into place, 5-second changover			Media roll o.d. (max)	109.22 mm
		Media parts offering	1300+ stock parts and custom (made-to-request) parts. All B30- and B33- series parts are compatible in the BradyPrinter i5300			Ink side	n/a (ribbon integrated in cartridge - guaranteed correct orientation to printhead)
Sensory and energy setting adjustments	No calibration required, Sensor, Speed and Heat settings are auto-set	Label width (cross-web)	6.35 mm to 107.95 mm (continuous linerless media) 6.35 mm to 101.98 mm (other media)			Label length (down-web)**	5.08 mm minimum (die-cut media). 12.70 mm minimum (continuous media)
Media width (cross-web, including liner)	18.03 mm to 107.95 mm	Media thickness	0.06 mm to 0.79 mm max (label media) 1.78 mm max (B-593 push-button media) 1.09 mm max (heat-shrink sleeves)			Media roll core i.d.	n/a (media roll integrated into drop-in cartridge)
Media roll winding	n/a	Ribbon length (max)	60.96 m	Ribbon roll core i.d.	n/a (ribbon roll integrated into drop-in cartridge)	Ribbon roll o.d. (max)	n/a (ribbon roll integrated into drop-in cartridge)
Media styles	All media is on an integrated cartridge roll with part data on the smart cell. Die-cut media, continuous media, tagstock liner-mounted, tagstock linerless, perforated materials, adhesive labels, heat-shrink sleeves size 094 and larger (single and double-sided with 2-pass print), self-laminating cable labels, cable ties and tags, raised panel push-button labels, rapido-style cable tags, PermaShield-style labels, pre-printed GHS labels, SFID outdoor-grade labels, direct thermal labels						
Media material types	PE (polyethylene), PET (polyester), PET (metallized), PU (polyurethane), PVC (vinyl), PVF (polyvinyl fluoride), PVDF (polyvinylidene fluoride), PP (polypropylene), PI (polyimide), polyamide, polyether polyurethane (Heatex™), raised panel push-button material, paper, tamper-evident and tamper-resistant materials, 8-10 year outdoor vinyl, 10-hour glow-in-the-dark material, retroreflective labels, printable floor marking tape, nylon and vinyl cloth, wash-down materials, extreme temperature laboratory materials, slides/lab-staining materials, other materials not listed						

Software and firmware						
Label creation software	Brady Workstation (v4.12 or newer) and Brady Workstation apps (latest updates)	WHQL certified Windows® drivers	Windows 7, 8, 8.1, 10, server 2008, 2008 R2, 2012, 2012 R2, 2017		Printer command language	BPL - scripting commands for sending scripts to the printer
Physical/operational characteristics						
Dimensions	284.48 mm W x 279.40 mm H x 401 mm D	Power consumption	20W standby/80W operating/200W max		Storage environment	-20 - 50°C/15 - 90% RH non condensing
Weight (without materials loaded)	15.0 kg	Power supply	101 - 240 VAC, 50/60 Hz, 3.5A		Operating environment	10 - 40°C/10 - 85% RH non condensing
Agency approvals	CE, FCC class A, cUL. Contact Brady for up-to-date list of environmental compliance information and agency approvals and/or marks covering over 75 countries (awarded or applied for)				Transport environment	-20 - 50°C/15 - 90% RH non condensing
Electronics						
Processor	32-bit 800 MHz clock rate	Memory (RAM)	512 MB	Internal battery	For internal date and time (RTC)	
Data storage when power off	Yes	Data storage (IFFS)	195 MB	SD card slot (SDHC, SDXC)	n/a	
Options/accessories						
Replacement printhead	User replaceable (to same dpi)	Auto cutter (on all models)	Built-in	Replacement print roller	115 mm width, user replaceable (T10 wrench required)	



Printers - 300 dpi

Article No.	Order Ref.	Description
151274	I5300-C-EU	BradyPrinter i5300 Industrial Label Printer - EU
322890	I5300-C-EU-BWS	BradyPrinter i5300 Industrial Label Printer - EU + Brady Workstation Suite
151272	I5300-C-NA	BradyPrinter i5300 Industrial Label Printer - NA
322892	I5300-C-NA-BWS	BradyPrinter i5300 Industrial Label Printer - NA + Brady Workstation Suite
151276	I5300-C-UK	BradyPrinter i5300 Industrial Label Printer - UK
322891	I5300-C-UK-BWS	BradyPrinter i5300 Industrial Label Printer - UK + Brady Workstation Suite

WiFi printers - 300 dpi

Article No.	Order Ref.	Description
151275	I5300-C-EU-WF	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - EU
322893	I5300-C-EU-WF-BWS	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - EU + Brady Workstation Suite
151273	I5300-C-NA-WF	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - NA
322895	I5300-C-NA-WF-BWS	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - NA + Brady Workstation Suite
151277	I5300-C-UK-WF	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - UK
322894	I5300-C-UK-WF-BWS	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - UK + Brady Workstation Suite

Printers - 600 dpi

Article No.	Order Ref.	Description
151283	I5300-600C-EU	BradyPrinter i5300 Industrial Label Printer - 600 dpi - EU
151281	I5300-600C-NA	BradyPrinter i5300 Industrial Label Printer - 600 dpi - NA
151285	I5300-600C-UK	BradyPrinter i5300 Industrial Label Printer - 600 dpi - UK
322896	I5300-600-EU-BWS	BradyPrinter i5300 Industrial Label Printer - EU + Brady Workstation Suite
322898	I5300-600-NA-BWS	BradyPrinter i5300 Industrial Label Printer - NA + Brady Workstation Suite
322897	I5300-600-UK-BWS	BradyPrinter i5300 Industrial Label Printer - UK + Brady Workstation Suite

WiFi printers - 600 dpi

Article No.	Order Ref.	Description
151284	I5300-600C-EU-WF	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - 600 dpi - EU
151282	I5300-600C-NA-WF	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - 600 dpi - NA
151286	I5300-600C-UK-WF	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - 600 dpi - UK
322899	I5300-600WF-EU-BWS	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - EU + Brady Workstation Suite
322902	I5300-600WF-NA-BWS	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - NA + Brady Workstation Suite
322900	I5300-600WF-UK-BWS	BradyPrinter i5300 Industrial Label Printer with Wi-Fi - UK + Brady Workstation Suite

The above part number descriptions do not reflect complete product data - refer to the specification sheet for complete details. i5300 printers accept all B30/B33 series media.



Accessories

Article No.	Order Ref.	Description
148703	MEDIA WIPER, BBP35-37, I5300	BBP35 and BBP37 Media Wiper
153661	I5300-PH-300D	i5300 Print Head 300 dpi
153662	I5300-PH-600D	i5300 Print Head 600 dpi
153663	I5300-PR-115MM	i5300 Print Roller
133251	PCK-6	Printer Cleaning Kit, Thermal Transfer Printers
142115	ASSY, PKG, ACCESSORY, STYLUS, PLA	Replacement Stylus 3 Pack

** Printheads can only be replaced with same dpi (300 with 300, or 600 with 600)

Learn more at www.bradyeurope.com/i5300

